

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0827	3	18	8 x 1	1	6	
0832	3	18	4 x 1	1		
0536	3	33	4 x 0.5	1		
0045	3	50	gebrochen	1	-	30° schräg
0741	3.5	18	4 x 1	1		Blech
0818	3.5	20.2	12 x 0.65	3	5	Flachbett-Stanzblech
0068	4	4	16 x 1	4	7	
0884	4	4	8 x 1	2	21	
0629	4	6	20 x 0.5	5	4	
0456	4	7	12 x 0.3	3	5	
0327	4	8	16 x 1.5	4	6	
0669	4	8	16 x 1.5	4	6	
0069	4	10	4 x 1	1	-	mit Längsmesser 4 mm
0126	4	20.2	12 x 0.3	3	5	
0618	4	24	4 x 1	1		
0305	4	31	8 x 1	2	5	
0300	4	39	4 x 0.4	1		
0552	4	50	4 x 1	1		
0133	4	80	4 x 1	1	-	
0091	4	86	gebrochen	1	-	
0223	4.4	22	8 x 1	2	5	
0372	4.5	17	12 x 0.5	3	10	
0579	4.5	18	4 x 1	3	5	
0290	4.5	36	8 x 0.5	2	5	
0058	4.5	75	4 x 1	1	-	doppelt
0141	4.5	75	4 x 1	1	-	doppelt
0213	4.5	87	4 x 0.5	1		
0636	5	5	12 x 0.5	3	7	Stanzblech
0641	5	5	12 x 0.5	3	11	
0651	5	5	12 x 0.5	3	11	Stanzblech m. Moosg.
0078	5	6	gebrochen	3	8	3-teilig
0048	5	7	spitz	4	5	ohne Abstand in Vorschubrichtung
0407	5	8	16 x 1	4	6	
0497	5	9	16 x 1	4	4	
0500	5	13	16 x 1	4	3	
0624	5	15	8 x 1	2	8	
0173	5	18	gebrochen	3	8	
0612	5	18.5	24 x 1	2	5	6-er Set, Perforation
0445	5	20	8 x 1	2	5	
0427	5	25	8 x 1	2	15	
0453	5	28	4 x 1	2	6	
0603	5	38	8 x 1	2	5	
0388	5	39	4 x 0.5	1		
0877	5	40	4 x 1	1		Blech
0241	5.5	57	4 x 0.5	1		
0319	6	6	16 x 1	4	8	
0490	6	9	16 x 0.5	3 + 1 LM	4	
0184	6	11	16 x 1	4	8	
0604	6	11	16 x 1	4	5	
0694	6	11	8 x 0.5	2	24	
0754	6	12.4	8 x 1	2	12.6	
0381	6	13.4	12 x spitz	3 + 1 Lm		Stanzblech
0009	6	15	gebrochen	2	4	
0114	6	15	12 x 0.5	3	2	Standard 01
0161	6	15	20 x 0.5	5	2	
0242	6	15	20 x 1.5	4	5	4 Nutzen + 1 Blindstück
0284	6	15	8 x 1	2	5	
0735	6	16	8 x 1	2	6	Blech
0470	6	19	16 x 1	4	3 / 6	
0571	6	19	8 x 1	2	5	
0616	6	19	12 x 1	3	5	
0127	6	20.2	12 x 0.5	3	5	

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0200	6	22	8 x 1.5	2	12	
0245	6	22	12 x 1.5	3	6	
0617	6	24	4 x 1	1		
0039	6	25	4 x 1	1	-	
0343	6	25	8 x 1	2	15	
0222	6	29	8 x 1	2	5	
0198	6	32.6	8 x 0.5	2	5	
0034	6	35	4 x 1	1	-	
0615	6	54	4 x 1	1		
0722	6	60	4 x 0.5	1		
0389	6	75	4 x 1	1		
0439	6.5	8.2	16 x 0.5	4	5	
0903	6.50	20.2	4 x 0.5	3	5	
0160	6.5	98	4 x 1	1		
0708	7	7	16 x 1	4	6	
0743	7	17	8 x 1	2	5	
0834	7	20	8 x 0.5	2	4	
0262	7	22	4 x 1	1		
0602	7	28	8 x 0.5	2	4	
0647	7	33	8 x 0.5	2	5	
0894	7	33	8 x 1	2	5	
0632	7	37	4 x 1	1		
0264	7	66	gebrochen	1		
0174	7	68	D=68	2	4.5	
0303	7.5	30	4 x 1	1		Spez.-Perforation
0498	7.9	11.8	8 x 1	2	5	
0509	8	8	8 x 0.5	2	22	
0517	8	8	12 x 1	3	10	
0585	8	8	16 x 1	4	3.25	
0463	8	15	4 x 2 / 4 x 0.5	2	10	
0786	8	15	8 x 0.5	2	10	
0328	8	16	16 x 1.5	4	3	
0029	8	20	8 x 1	2	4	
0631	8	25	4 x 1	1		
0214	8	30	4 x 0.5	1		
0625	8	33	8 x 0.5	2	5	
0623	8	35	8 x 0.5	2	5	
0113	8	50	4 x 0.5	1	-	
0812	8	50	4 x 1	1		
0185	8	75	4 x 0.4	1		
0315	8.2	30	8 x 1.5	2	2	
0883	8.50	32.2	8 x 1	2	3	mit Lichtmarke 8.5 x 10 mm
0166	8.5	32.6	8 x 1	2	5	
0053	8.5	45	4 x 0.5	1	-	
0578	8.5	61	4 x 1	1		
0878	9	9	8 x 1	2	10	
0215	9	16	8 x 0.5	2	10	
0373	9	17	12 x 1	3	10	
0437	9	17.3	16 x 1.25	3 x Lm	10 / 1.5	
0382	9	18	8 x 1	2	4	
0843	9	18	8 x 1	2	7	
0879	9	18	8 x 0.5	2	10	
0293	9	19	12 x 1.5	3	5	
0601	9	19	8 x 1.5	2	5	
0861	9	20	12 x 1.5	3	3	
0532	9	22	12 x 0.5	3	6	
0404	9	26	8 x 1	2	5	
0338	9	27	12 x 1.5	3	1.5	
0534	9	27	8 x 1.5	2	1.5	
0047	9	28	8 x 1	2	2	2 Nutzen nebeneinander
0216	9	28	12 x 1.5	3	1.5	
0551	9	30	8 x 1	2	4	

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0128	9	32.6	8 x 1	2	5	
0371	9	34	8 x 1	2	4	
0860	9	35	4 x 1	1		
0392	9	37	4 x 1	1		
0295	9	45	4 x 1.5	1		
0281	9	51	4 x 2	1		
0312	9	84	4 x 1.5	1		
0212	9	87	4 x 1.5	1		
0140	9	89	4 x 1	1	-	
0508	9.1	23.3/22.32	102.33			Stanzblech
0817	9.35	9.35	36 x 0.5	9	2.5	Flachbett-Stanzblech
0514	9.5	18.5	8 x 1	2	5	
0144	9.5	24	8 x 1	2	7	
0301	9.5	73.5	gebrochen	1		
0046	10	10	12 x 1	3	5	
0737	10	10	8 x 0.5	2	15	
0648	10	13	12 x 1	3	4	
0671	10	13	12 x 1.5	3	4	
0460	10	18	8 x 1	2	6	
0116	10	20	8 x 0.5	2	4	Standard 03
0847	10	20	8 x 1.5	2	5	
0332	10	22	12 x 1.5	3	3	
0042	10	25	4 x 2	1	-	
0162	10	25	12 x 2	3	3	
0441	10	25	8 x 1	2	4	
0176	10	27	gebrochen	2	5	
0077	10	30	4 x 1	1	-	
0172	10	30	12 x 1,5	3	5	
0257	10	33	8 x 0,5	2	4	
0530	10	40	4 x 1	1		
0531	10	40	4 x 1	1		mit Perforation
0711	10	42	4 x 1.5	1		Sicherheitsstanzung
0744	10	42	8 x 1.5	2		Blech mit Sicherheitsstanzung
0778	10	42	4 x 1.5	1		
0406	10	46	4 x 1	1		
0805	10	50	4 x 1	1		
0598	10	75	4 x 1	1		
0652	10	75	4 x 1	1		mit Positionsmarke
0217	10	80	4 x 1	1		Perforationslinie
0895	10	89	4 x 1.5	1		
0006	10	100	4 x 1	1	-	
0016	10	107	4 x 1	1	-	
0592	11	6	20 x 1	5	3.2	
0432	11	17	12 x 1.5	3	5	
0285	11	30	8 x 1.5	2	4	
0882	11	38	4 x 1	1		
0869	11	40	4 x 1	1		
0231	11	54	4 x 1	1		
0830	11	88	4 x 1.5	1		
0554	11	95	4 x 1.5	1		
0723	11	110	4 x 1	1		
0674	11.1	46	4 x 1	1		
0599	11.5	25	8 x 1	2	3	
0845	12	12	4 x 1	1		
0863	12	12	4 x 2	1		
0899	12	16	8 x 1.6	2	9	Lichtmarke
0706	12	18	8 x 1	2	4	
0282	12	19	12 x 2	3	5	
0583	12	30	8 x 2	2	4	
0320	12	34	4 x 1	1		
0489	12	34	8 x 1	2	4	
0619	12	40	8 x 1	2	4	

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0739	12	54	4 x 1	1		
0171	12	60	4 x 1.5	1		
0477	12	77	8 x 1	2	1.5	
0541	12	80	4 x 1.5	1		
0768	12	89	4 x 0.5	1		
0655	12	90	4 x 2	1		
0717	12	98	4 x 1.5	1		
0224	12	100	4 x 1.5	1		
0280	12.4	20	4 x 1,5	2	5	
0331	12.4	23	8 x 1.3	2	4	
0288	12.4	25	8 x 1.5	2	5	
0062	12.5	25	8 x 0.2	2	5	
0178	12.5	25	12 x 0.2	2	5	mit Synchronmarke 10 x 12.5 mm
0183	12.5	25	8 x 1	2	5	
0584	12.5	27	8 x 1.5	2	5	
0746	12.5	37	8 x 0.5	2	5	
0063	12.5	50	4 x 0.2	1	-	
0155	12.5	83	4 x 0.5	1		
0622	12.7	25.4	12 x 0.5	3	2.5	
0672	12.7	25.4	4 x 1	1		
0852	12.7	25.4	12 x 1	3	1.91	
0897	12.7	50.8	4 x 1	1		
0900	13.00	13	12 x 1	3	2.5	
0709	13	19	8 x 1.5	2	5	
0464	13	24	8 x 1.3	2	5	
0023	13	26	4 x 1	1	-	
0149	13	26	8 x 1.5	2	3	
0383	13	27	8 x 1.5	2	4	
0089	13	29	4 x 1	2	5	
0013	13	37	4 x 1.5	1	-	
0027	13	45	4 x 1	1	-	
0638	13	50	4 x 1	1		
0715	13	70	4 x 1	1		
0420	13.5	13.5	12 x 1	3	5	
0473	13.5	54	4 x 1	1		
0597	13.7	78	4 x 0.5	1		
0596	13.7	100	4 x 0.5	1		
0248	14	20	12 x 1	3	5	
0252	14	20	8 x 1	2	4	
0662	14	23	8 x 1.5	2	10	
0656	14	27	4 x 1.5	1		
0335	14	35	4 x 1	1		
0170	14	38	8 x 1.5	2	5	
0243	14	40	8 x 1.5	2	6	
0465	14	40	8 x 1	2	4	
0609	14	40	4 x 1	1		
0657	14	40	4 x 1.5	1		
0054	14	45	4 x 0.5	1	-	
0679	14	45	4 x 0.5	1 + LM	2	mit Positionsmarke
0664	14	60	4 x 2	1		
0511	14	68	4 x 1.5	1		
0663	14	79	4 x 2	1		
0210	14.5	80	4 x 1.5	1		
0634	15	8	20 x 1	5	5	
0085	15	15	8 x 0.5	2	8	
0294	15	15	12 x 1	3	4	
0697	15	15	12 x 3	3	4	
0784	15	15	8 x 1	2	15	
0789	15	15	4 x 2	1		
0304	15	17	6 x 1	2	5	
0680	15	20	4 x 1	2	4	
0887	15	25	4 x 2	1		

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0816	15	27	4x1	1		
0137	15	30	8 x 0.5	2	3	
0260	15	30	12 x 1.5	3	4	
0275	15	30	gebrochen	1		
0276	15	30	8 x 1	2	5	
0825	15	30	4 x 2	1		
0888	15	35	4 x 2	1		
0129	15	39	8 x 1.5	2	3	
0148	15	39	4 x 1	1	-	
0158	15	39	8 x 1	2	3	
0074	15	40	4 x 1	1	-	2 Ausschnitte 2 x 25 mm
0608	15	40	4 x 1	1		
0896	15	43	4 x 1	1		
0467	15	45	8 x 1	2	4	
0630	15	46	4 x 1	1		
0272	15	50	4 x 1	1		
0302	15	51	gebrochen	1		
0273	15	55	4 x 1	1		
0695	15	55	8 x 1.5	2	4	Sicherheitsstanzung
0696	15	55	8 x 1.5	1		Sicherheitsstanzung
0386	15	75	4 x 3	1		
0369	15	84	4 x 1.5	1		
0031	15	95	4 x 2	1	-	
0387	15	95	4 x 3	1		
0014	15	100	4 x 2	1	-	
0567	15	100	4 x 1.5	1		
0633	15.5	48.5	4 x 1	1		
0804	16	5	12 x 1	3	5	
0435	16	16	4 x 0.3	2	8	
0731	16	20	4 x 1	1		
0246	16	22	8 x 1	2	3	
0760	16	26	4 x 1.5	1		
0325	16	27	12 x 1.5	3	1.5	
0487	16	27	4 x 1.5	1		
0204	16	28	12 x 1.5	3	1.5	
0859	16	28	8 x 1.5	2	7	
0873	16	43	4 x 1	1		
0150	16	46	4 x 1.5	1	-	
0202	16	46	4 x 2.5	1		
0188	16	50	4 x 2.5	1		
0363	16	53	4 x 1.5	1		
0134	16	54	gebrochen	1	-	
0792	16	56.4	4 x 2	1		
0398	16	58	4 x 1	1		
0038	16	75	4 x 2	1	-	
0814	16	101.5	4 x 0.3	1		
0446	17	22	8 x 1	2	3	
0450	17	22	12 x 1	3	5	
0448	17	23	8 x 1	2	3	
0800	17	32	4 x 1.5	1		
0906	17.00	37	4 x 1.5	1	0	
0056	17	40	4 x 1.2	1	-	
0059	17	58	4 x 2	1	-	
0159	17	58	8 x 2	2	1	
0102	17	63	4 x 1.5	1	-	
0811	17.3	20	3 x 1	1		Dreieck
0658	17.5	45.5	4 x 2	1		
0317	17.5	52.4	4 x 1.6	1		
0721	18	20	4 x 3	1		
0801	18	22	8 x 0.5	2	4	
0659	18	30	4 x 2	1		
0666	18	30	4 x 2	1		

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0193	18	32	4 x 1	1		
0028	18	45	4 x 1	1	-	
0240	18	45	8 x 1.5	2	4	
0661	18	46	4 x 2	1		
0057	18	50	4 x 1.2	1	-	
0277	18	50	4 x 1.5	1		
0055	18	52	4 x 1.2	1	-	
0421	18	52	4 x 2	1		
0665	18	60	4 x 2	1		
0833	18	61	4 x 1	1		
0546	18	66	4 x 2	1		mit Lichtmarke 4 x 7 mm
0471	18	70	4 x 0.5	1		2 Längs-Perforationen
0225	18	100	4 x 1.5	1		
0197	18	116	4 x 2	1		
0330	18.4	42.7	4 x 1.5	1		
0365	19	6	24 x 1	6	4 x 2, 1 x 4	
0793	19	22	4 x 0.5	1		
0250	19	24	8 x 1	2	7	
0379	19	40	4 x 2	1		
0865	19	44	4 x 2	1		
0880	19	54	4 x 2	1		
0507	19	59	4 x 1	1		mit Positionsmarke
0545	19	59	4 x 2	1		mit Lichtmarke 4 x 7 mm
0820	19	80	1	1		Kabeletikette 2 Perforationen, Perfo nach jeder Etikette
0569	19	100	4 x 1.5	1		
0850	19.05	38.10	8 x 1.5	2	3.81	
0344	19.5	19.5	8 x 1.2	2	19.5	
0086	19.5	24	8 x 0.5	2	6	
0071	19.5	29.5	4 x 0.5	1	-	
0472	19.5	29.5	4 x 2	1		
0871	19.5	29.5	8 x 2	2	4	
0856	19.5	50	8 x 1.5	2		
0654	20	8	20 x 1	5	3	
0849	20	10	8 x 1.5	2	15	
0017	20	14	8 x 1	2	4	
0191	20	20	Ecken aufgeschnitten	1		Perforationslinie
0486	20	20	16 x 1	4	1.5	
0510	20	20	8 x 2	2	5	
0678	20	20	12 x 1	3	3	
0756	20	25	4 x 1.5	1		
0808	20	30	4 x 2	1		
0419	20	36	4 x 4	1		
0258	20	38	8 x 1.5	2	5	
0593	20	38	4 x 1.5	1		
0018	20	40	4 x 1	1	-	
0117	20	40	8 x 1	2	4	Standard 04
0181	20	40	4 x 1	1		mit Perforationslinie
0261	20	40	4 x 4	1		
0704	20	40	4 x 3	1		
0314	20	41	4 x 1.5	2	2	
0313	20	42	gebrochen	1		
0208	20	43	8 x 1.5	2	1.5	
0356	20	44	4 x 1	1		
0555	20	45	4 x 1.5	1		
0620	20	45	8 x 0.5	2	4	
0167	20	47	4 x 1.5	1		
0021	20	50	4 x 2	1	-	
0274	20	50	4 x 2	1		Perforationslinie
0136	20	56	4 x 1.5	1	-	
0122	20	60	4 x 1.5	1	-	Standard 1
0720	20	60	4 x 3	1		
0209	20	62	4 x 1.5	1		

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0139	20	65	4 x 4	1	-	
0475	20	70	4 x 2	1		
0094	20	75	4 x 2	1	-	
0482	20	75	4 x 1	1		mit Positionsmarke
0105	20	90	gebrochen	1	-	Kanten gebrochen
0189	20	90	4 x 2.5	1		
0394	20	100	4 x 3	1		
0727	20	106	4 x 1.5	1		
0182	20	43/8	8 x 1	2	5	
0538	21	45.5	4 x 1	1		
0670	21	45.6	4 x 1.5	1		
0349	21	50	4 x 5	1		
0299	21	120	4 x 2	1		
0772	21.5	42	4 x 1.5	1		
0037	21.5	51.5	4 x 1.5	1	-	
0411	21.8	21.8	16 x 1	4	4	
0339	21.8	75.8	6 x 1	1		Einseitige Einkerbung
0493	22	4	24 x 0.5	6	4 x 0.4 / 1 x 1.0	
0309	22	27	12 x 1.5	3	1.5	
0205	22	28	12 x 1.5	3	1.5	
0080	22	52	4 x 1	1	-	
0180	22	52	4 x 2	1		mit Perforationslinie
0826	22	55	4 x 3	1		
0691	22	60	4 x 3	1		
0515	22	63	4 x 1	1		
0660	22	64	4 x 2	1		
0764	22	65	4 x 3	1		
0194	22	75	4 x 2	1		
0211	22	83	4 x 1.5	1		
0237	22	85	4 x 0.5	1		
0449	22	100	4 x 3	1		
0111	22.6	55.5	4 x 1	1	-	
0874	23	8	4 x 1	1		
0846	23	32	4 x 1	1		
0115	23	40	4 x 6	1	-	
0228	23	40	4 x 1.5	1		
0232	23	40	8 x 1.5	2	5	
0364	23	40	4 x 3	1		Perforationslinie
0876	23	43	4 x 1.5	1		
0297	23	44	4 x 1	1		
0734	23	45	4 x 1.5	1		
0559	23	51	4 x 1	1		Kabeletiketten
0368	23	53	4 x 1.5	1		
0503	23	72	4 x 2	1		
0770	23.5	25	4 x 0.5	1		
0769	23.5	51.5	4 x 1.25	1		
0690	24	46	8 x 1	1	3	2 Nutzen in Laufrichtung
0819	24	46	4 x 1	1		
0265	24	64	4 x 2	1		
0787	24	70	4 x 4	1		
0802	24	70	4 x 4	1		
0157	24	75	4 x 1.5	1		
0773	24.3	79.3	4 x 3	1		
0145	24.5	20	8 x 1	2	5	
0346	24.5	78.6	4 x 1.5	1		
0775	24.5	79.5	4 x 3	1		
0785	25	11.5	8 x 4	2	13.5	
0454	25	25	8 x 0.3	2	5	
0889	25	35	4 x 2	1		
0855	25	40	4 x 2	1		
0774	25	41	4 x 1	1		
0279	25	45	gebrochen	1		

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0459	25	45	8 x 2	2	5	
0780	25	45	8 x 2	2	10	
0120	25	50	8 x 1.5	2	4	Standard 05
0177	25	50	4 x 1.5	1		mit Perforationslinie
0255	25	50	4 x 3.5	1		
0539	25	50	4 x 2.6	1		
0079	25	56	4 x 1	1	-	
0125	25	60	4 x 1	1	-	
0824	25	60	4 x 2	1		
0607	25	62	4 x 1	1		
0352	25	70	4 x 2	1		
0898	25	75	4 x 2	1	1	Lichtmarke
0251	25	79	4 x 1.5	1		
0083	25	90	4 x 3	1	-	
0867	25	100	4 x 2	1		
0570	25	110	4 x 5	1		
0244	25	Dreieck		3	2	
0544	25.4	50.8	4 x 2	1		mit Lichtmarke 4 x 7 mm
0853	25.4	50.8	4 x 2	1		
0422	25.5	57.5	2 x 2.5 / 2 x 4.5	1		
0011	26	26	4 x 1	1	-	
0311	26	37	8 x 1	2	6	
0540	26	37	8 x 1	2	2	
0438	26	38	8 x 2	2 + Lm	1.5	
0020	26	42	4 x 2	1	-	
0165	26	42	8 x 2	2	2	
0783	26	45	4 x 1	1		
0019	26	52	4 x 2.5	1	-	
0169	26	52	2 x 1	1		Halbkreis
0590	26	60	4 x 3	1		
0443	26	65	4 x 3	1		
0543	26	68	4 x 1	1		spez., mit Loch
0108	26	70	4 x 3	1	-	
0642	26	90	4 x 1	1		
0676	26	90	4 x 2	1		
0738	27	38	8 x 1.5	2	5	
0777	27	51.3	4 x 1.25	1		
0563	27	58	4 x 2.5	1		
0537	27	70	4 x 1.5	1		
0401	27	117	4 x 0.5	1		
0535	28	6	4 x 0.5	1		
0307	28	27	12 x 1.5	3	1.5	
0026	28	28	4 x 1	1	-	
0206	28	28	12 x 1.5	3	1.5	
0904	28.00	40	4 x 0.5	1	0	
0101	28	45	4 x 1.5	1	-	
0336	28	54	1 x 45	1		
0397	28	57	4 x 3	1		
0104	28	101.6	4 x 1	1	-	
0716	29	69	4 x 2	1		Positionsmarke für GX430
0491	29	70	4 x 2	1		
0693	29	80	4 x 1.5	1		
0393	29.8	66.8	2 x 0.5 / 2 x 2.0	1		
0635	30	8	20 x 1	5	5	
0022	30	15	4 x 1	1	-	
0752	30	37	4 x 1	1		Kabeletiketten Druckfläche 30x11
0501	30	40	4 x 1	1		
0527	30	40	4 x 0.5	1		Stanzblech 2 Loch
0528	30	40	4 x 0.5	1		Stanzblech 1 Loch
0681	30	40	4 x 3	1		
0337	30	45	4 x 1.5	1	-	
0483	30	45	8 x 1	2	4	mit Positionsmarke

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0779	30	49	4 x 1	1		Kabeletiketten Druckfläche 30x14
0096	30	50	4 x 1.5	1	-	
0761	30	50	4 x 1	1		
0359	30	53	4 x 1.5	1	-	
0762	30	55	4 x 1.25	1		
0036	30	60	4 x 2	1	-	
0707	30	60	4 x 2	1	1	Lichtmarke
0700	30	61	4 x 3	1		Blech
0518	30	65	4 x 1.5	1		
0081	30	68	4 x 1.5	1	-	
0474	30	68	4 x 1.5	1		mit Positionsmarke
0130	30	70	4 x 2.5	1	-	
0143	30	70	4 x 2.5	1	-	
0032	30	73	4 x 2	1	-	
0713	30	77	4 x 2	1		
0238	30	80	4 x 0.5	1		
0558	30	80	4 x 2	1		
0790	30	80	8 x 2	1		2-teilig
0095	30	85	4 x 3	1	-	
0549	30	100	4 x 2.5	1		
0565	30	100	4 x 2	1		
0848	30	110	4 x 3	1		
0469	30	115	4 x 2.5	1		Spezielle Sicherheits-Perforation
0890	31	37	4 x 2	1		
0348	31	43	Spezial	1		
0060	31	47	4 x 1.5	1	-	
0413	31	80	4 x 1	1		
0822	31.5	47		1		Sonderform Blech
0219	31.7	41.8	4 x 1.5	1		
0851	31.75	69.85	4 x 2	1		
0192	32	42	4 x 1.5	1		
0718	32	80	4 x 2	1		
0466	32	85	4 x 2.5	1		
0015	32	116	4 x 1	1	-	8 LED Aussparungen
0152	33	35	4 x 1.5	1		
0650	33	62	4 x 1.5	1		
0524	33	65	4 x 2.5	1		
0440	33	80	4 x 2	1		
0525	33	90	4 x 2.5	1		
0423	33.5	78	2 x 2.5 / 2 x 5	1		
0485	34	9	8 x 0.5	2	2	
0782	34	12	8 x 1	2	8	
0462	34	34	8 x 0.3	2	5	
0207	34	37	8 x 1.5	2	8	
0103	34	60	4 x 1.5	1	-	
0725	34	60	4 x 5	1		
0088	34.5	72.5	4 x 1.5	1	-	
0146	35	29	4 x 1.5	1	-	
0798	35	31	8 x 2	2		
0412	35	32	4 x 1	1		
0308	35	41	8 x 1,5	2	2	
0227	35	43	8 x 1.5	2	1.5	
0384	35	46	4 x 3	1		
0008	35	50	4 x 2	1	-	
0396	35	55	4 x 1	1		
0698	35	62	4 x 1	1		Kabeletiketten
0581	35	70	4 x 2	1		
0699	35	82	4 x 1	1		Kabeletiketten
0705	35	88	4 x 1	1		Kabeletiketten
0098	35	88.6	4 x 1.5	1	-	
0360	35	90	4 x 1	1	-	
0828	35	93		1		Sonderform Blech

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0580	35	95	4 x 2	1		
0049	35	100	4 x 2	1	-	
0683	35	105	4 x 3	1		
0844	35	105	4 x 1	1		Kabeletiketten
0759	35	115	4 x 2.5	1		
0007	35.6	101.6	4 x 1	1	-	
0803	36	23.5	8x 1	2	4	
0430	36	48	4 x 2	1		
0767	36	62	4 x 4	1		
0283	36	70	4 x 2.5	1		
0891	36	75	4 x 2	1		
0118	36	80	4 x 2	1	-	
0286	37	34	8 x 1.5	2	11	Lücke 11mm
0287	37	34	8 x 1.5	2	8	Lücke 8 mm
0902	37.00	53	4 x 2	1		
0610	37	62.5	4 x 2	1		
0179	37	70	4 x 1.5	1		
0380	37	74	4 x 1.5	1		
0495	38	50	4 x 0.5	1		
0203	38	60	4 x 1.5	1		
0566	38	100	4 x 2.5	1		
0499	38	118		1		mit Perforation, spez.
0646	38.1	50.8	4 x 1.5	1		
0375	38.1	90.5	4 x 2	1		
0196	39	35	4 x 2	1		
0385	39	46	4 x 3	1		
0151	39	99	4 x 3.5	1		
0461	40	19	8 x 1.5	2	10	
0686	40	35	4 x 1	1		
0416	40	40	4 x 1.5	1		
0733	40	40	4 x 1.5	1		
0684	40	50	8 x 1.5	2	5	
0366	40	54	4 x 2	1		
0100	40	55	4 x 2	1	-	
0310	40	60	4 x 3	1		
0494	40	62	4 x 0.5	1		
0835	40	62	4 x 1	1		Kabeletikette mit Abreissperfo
0067	40	65	4x 2	1	-	
0353	40	70		1		Kanten gebrochen
0806	40	70	4 x 2	1		
0736	40	78	4 x 2	1		
0318	40	80	4 x 2	1		
0841	40	80	4 x 1	1		
0611	40	82	4 x 4	1		
0109	40	85	4 x 1	1	-	
0402	40	90	4 x 2.5	1		spez., Perforation
0526	40	90	4 x 2.5	1		
0788	40	95	4 x 2	1		
0550	40	97	4 x 2	1		
0041	40	100	4 x 2.5	1	-	mit Loch
0084	40	100	4 x 2.5	1	-	
0573	40	110	4 x 1.5	1		
0688	40	115	4 x 2	1		
0513	41	18	12 x 1	3	2	
0329	41.5	31 / 28	8 x 1.5	2	2	
0745	42	42	4 x 2	1		
0582	42	50	4 x 1.5	1		
0271	42	62	gebrochen	1		
0044	42	84	4 x 1	1	-	
0613	42	102	4 x 2	1		
0776	43	42	4 x 1	1		
0434	44	44	4 x 0.3	1		

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0692	44	51	4 x 3	1		Kabeletiketten
0842	44	57	4 x 2	1		
0795	44	64	4 x 2	1		Querperforationslinie
0589	44	70	4 x 2	1		
0233	44	72	4 x 3	1		
0051	44	102		1	-	Wappen
0771	44.3	66.3	4 x 6	1		
0766	44.5	66.5	4 x 6	1		
0757	44.5	100	4 x 2	1		
0478	45	30	8 x 1	2	4	
0823	45	34		1		Sonderform Blech
0066	45	35	4 x 2	1	-	mit Perforationsmesser
0266	45	45	4 x 2	1		
0391	45	50	4 x 2	1		
0376	45	60	4 x 1.5	1	-	2-teilig
0425	45	60	4 x 2	1		
0516	45	65	4 x 1.5	1		
0442	45	75	4 x 3	1		
0099	45	80	4 x 2.5	1	-	
0577	45	100	4 x 3	1		
0600	45	100	4 x 2	1		
0765	45.6	50.6	4 x 4	1		
0433	46	10	4 x 1	1		
0481	46	24	8 x 1	2	4	
0866	46	70	4 x 1.5	1		
0201	47	33	8 x 0.5	2	5	
0221	47	58	4 x 1.5	1		
0763	47	67.5	4 x 6	1		
0076	47.5	88.5	4 x 1.5	1	-	
0370	48	74	4 x 1.5	1		
0837	50	18	4 x 1.5	1		
0147	50	30	4 x 1.5	1	-	
0082	50	40	4 x 1.5	1	-	
0278	50	45	gebrochen	1		
0594	50	45	4 x 2	1		
0907	50.00	48	4 x 1.5	1	0	
0591	50	60	4 x 3	1		
0675	50	65	4 x 2	1		
0796	50	67	4 x 1.5	1		
0090	50	68	4 x 2	1	-	Perforationslinie
0142	50	70	4 x 2.5	1	-	
0097	50	75	4 x 2.5	1	-	
0040	50	80	4 x 2	1	-	
0488	50	85	4 x 2	1		
0361	50	90	4 x 1	1	-	
0751	50	94	4 x 1	1		
0154	50	100	4 x 2.5	1		
0542	50	110	4 x 1.5	1		
0643	50.8	88.9	4x 3.5	1		
0644	50.8	114.3	4 x 1.5	1		Stanzblech
0334	51	37	8 x 1.5	2	2	
0030	51	64	4 x 2	1	-	
0649	51	76	4 x 2	1		
0005	51	83	4 x 2	1	-	
0292	52	24	12 x 2	3	5	
0533	52	24	8 x 2	2	5	
0121	52	52	8 x 1.5	2	3	Standard 07
0291	52	74	4 x 2	1		
0732	52	76	4 x 2	1		
0093	52	105	4 x 3	1	-	
0347	53	68.8	4 x 3	1		
0728	54	60	4 x 2	1		

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0568	54	100	4 x 2	1		
0892	55	55	4 x 2	1		
0522	55	60	4 x 2	1		
0677	55	85	4 x 2	1		
0809	55	85	4 x 2	1+ LM		mit Lichtmarke 4 x 8 mm
0506	55	95	4 x 2.5	1		
0458	55	110	4 x 1	1		
0626	56	20	12 x 1.5	3	3	mit Positionsmarke
0791	56.4	91.4				Blech
0378	58	90	4 x 2.5	1		
0024	59	69	2 x 1.5	1	-	2 x Ecken abgeschnitten
0628	60	30	4 x 2	1		
0405	60	40	8 x 1.5	2	5	
0726	60	40	4 x 1	1		
0742	60	40	4 x 2	1		
0606	60	45	4 x 2	1		
0881	60	58	4 x 1.5	1		
0712	60	60	4 x 2	1		
0298	60	70	4 x 2.5	1		
0512	60	80	4 x 2	1		
0012	60	88	4 x 4		-	
0857	60	90	4 x 2	2		
0730	60	94	4 x 2	1		
0110	60	100	4 x 1.5	1	-	
0838	60	105	4 x 2	1		
0553	61	39	4 x 2	1		
0520	62	72	2 x 44	1		Stanzblech
0645	63.5	114.3	4 x 1.5	1		Stanzblech
0333	64	20	12 x 1.5	3	5	
0468	64	64	4 x 1.5	1		
0452	64	70	4 x 1.5	1		
0523	64	85	4 x 2.5	1		
0673	64	94	4 x 3	1		
0758	65	10	4 x 1	1		
0070	65	100	4 x 2.5	1	-	
0218	65	105	4 x 0.5	1		3-teilig
0447	65	113	4 x 5	1		
0296	66	53	4 x 2	1		
0414	66	66	4 x 1	1		
0724	66	92	4 x 2	1		
0087	69	56	4 x 1	1	-	
0457	69	84	spitz	3-teilig		Stanzblech
0637	70	40	4 x 1.5	1		
0750	70	50	4 x 1.5	1		
0504	70	60	4 x 1	1		
0687	70	70	4 x 1.5	1		Lichtmarke
0868	70	70	4 x 1.5	1		
0270	70	75	4 x 2			
0595	70	90	4 x 2	1		
0572	70	95	4 x 3	1		
0123	71	70	4 x 2	1	-	Standard 8
0289	72	20	8 x 1.5	2	5	
0168	72	26	4 x 2.5	1		
0050	72	40	4 x 2	1	-	
0112	72	50	4 x 2	1		ersetzt die 2-bahnige
0519	72	72	4 x 1.5	1		
0187	72	95	4 x 4	1		
0124	72	106	4 x 2	1	-	Standard 9
0367	72.5	100	4 x 2.5	1		
0444	73	100	4 x 1.5	1		
0653	75	70	4 x 2	1		
0586	75	100	4 x 2	1		Stanzblech

Nummer	Länge / Höhe Vorschub	Breite	Radien (in mm)	Nutzen	Zwischenraum Breite (in mm)	Bemerkung
0749	75	100	spitz	1		Blech
0199	77	60	24 x 1.5	6		
0374	78	74	4 x 2	1		Stanzblech
0562	78	77	4 x 2	1		Stanzblech
0502	80	30	8 x 1	2	5	Stanzblech
0719	80	50	4 x 2	1		Blech
0794	4/1.7	4/5.7	8x0.5+8x0.3	4	5	Blech
0431	3 / 6	39 / 16	4 x 0.3 / 0.5	1 x LM		
0484	15/15/15	Lm 14 x 9	12 x 0.5	2 / 3	3 + Lm	
0253	20 / 20	35.5 / 45		2	2	
0418	22/3.5/3.5	16/11/11	8 x 1 / 16 x 0.5	6	4	2 Set
0263	26/26	52/10	4x1,5 / 4x2	2	5	
0268	30/30	38/10	8 x 1,5	2	5	
0267	30/30	60/10	8 x 2	2	5	
0747	45 / 65	110	8 x 1			Kabeletiketten 45x45 mit Schutzlaschen!
0395	Dreieck	15 x 15 x 15	3 x 1	1		
0621	LM 20 x 14	KS 20 x 58	diverse	2	5	
0324	Rund	D = 10		4	5	
0839	Rund	D = 10		2	30	
0864	Rund	D = 10		2	4	mit Lichtmarke 10 x 14 mm
0574	Rund	D = 10 + Lm		5 + Lm	5	
0061	Rund	D = 11		3	7	3 Nutzen nebeneinander
0306	Rund	D = 11	4 x 1	3	4.5	
0323	Rund	D = 12.7/10		2	10	
0351	Rund	D = 15		3	3	
0748	Rund	D = 15		2	6	
0052	Rund	D = 15 / 8.5		3	3	3 Nutzen nebeneinander
0755	Rund	D = 18		1		
0505	Rund	D = 18/10		2	5	Stanzblech
0092	Rund	D = 19		2	10	Abstand 32
0164	Rund	D = 19	4 x 1	4	1.5	
0342	Rund	D = 20		4	5	
0821	Rund	D = 20		1		Blech+ Lichtmarke 20 x 20 mm
0668	Rund	D = 25		2	5	Kreis mit Loch D = 14.4
0529	Rund	D = 28/22		1		Stanzblech
0355	Rund	D = 29, d = 9		1		mit Lichtmarke
0588	Rund	D = 30		2	2	
0230	Rund	D = 30 / D = 6		1		
0229	Rund	D = 34		1		
0640	Rund	D = 38		1		
0350	Rund	D = 4		4	12	
0417	Rund	D = 40		1		
0340	Rund	D = 5 / LM 5 x 8		1 + 5	5	
0358	Rund	D = 5.5		6	3	
0521	Rund	D = 52		1		
0035	Rund	D = 60		1	-	Abflachung 55 mm
0220	Rund	D = 68		1		
0186	Rund	D = 68 mm		1		mit Perforationslinie
0190	Rund	D = 79.4		1		
0043	Rund	D = 8		4	4	
0254	Rund	D = 8		5	2.5	
0451	Rund	D = 8		5		
0901	Rund	D = 12		4	3	mit Lichtmarke 10 x 14 mm